



- Municipal
- Commercial
- Government

Turn-key solutions to control traffic patterns, parking enforcement and site security



800•642•7289

Copyright © 2001

Model DGLK-0075

Keyless Entry Access Systems

- **Brushed Stainless Steel Face Plate**
- **Illuminated Keypad**
- **Vandal Resistant Construction, Indoor or Outdoor Use**
- **Up to 75 codes**

Model DGLK-0075 offers a wide range of standard features normally not found in other digital locks, such as built in lighting, two relays, time clock capability, relay hold feature, and 4 or 5 digit entry codes on every system. Each DGLK-0075 is housed in a rugged steel box, using a stainless steel faceplate with a metal keypad to make it vandal resistant. The DGLK-0075 is a stand-alone keyless entry system for outdoor use

Standard Features:

- Strikes & Out feature triggers system lockout when invalid codes are entered.
- Time clock feature can lock out individual codes at designated times
- Quick erase feature clears all memory entry codes at one time
- Keypad programmable using programming access codes
- EEPROM memory will not lose programmed codes
- Vandal resistant housing and metal keypad
- Built-in hood & lighting on every system
- Two relays for dual relay activation.
- Four or Five digit entry codes
- Slave keypad capability
- Single AND dual relay control:
 - Momentarily activates relay 1
 - Momentarily activates relay 2
 - Momentarily activates relay 1 & 2
 - Hold open (latch) relay 1
 - Hold open (latch) relay 2
 - Hold open (latch) relay1&2



DGLK-0075

Specifications:

- One Year Warranty
- Capacity: 75 entry codes.
- Powder coated black steel box
- Power input: 12 VAC or 12 VDC
- Entry Code Length: 4 or 5 digits
- Relay strike time 1 to 99 seconds
- Stainless steel face plate and keypads
- Strikes & Out count 1 to 10 (may be turned off.)